



ST Series



SPECIFICATIONS

Stationary Pressure Washer

Model	GENERAL				ELECTRICAL			BURNER SYSTEM			DIMENSIONS/LBS.			
	GPM	PSI	HP	Drive	Volt	AMP	Ph.	BTU GAS	BTU DIESEL	Max. Temp.	L	W	H	LBS.
ST-303	3	300	.75	Belt	120	10	1	440,000	420,000	300°F/ Steam	56"	24"	55"	730
ST-2304	4	2300	6	Belt	208/230	20/15	1/3	400,000	350,000	210°F	56"	24"	55"	776
ST-3004	4	3000	8/7.5	Belt	208/230	30/25	1/3	400,000	350,000	210°F	56"	24"	55"	794
ST-2305	5	2300	8/7.5	Belt	208/230	30/25	1/3	400,000	420,000	210°F	56"	24"	55"	848
ST-3005	5	3000	10	Belt	208/230	30	3	400,000	420,000	210°F	56"	24"	55"	848
ST-304	4	300	2	Belt	120	15	1	770,000	726,000	300°F/ Steam	64"	28"	58"	1030
ST-3006	6	3000	15	Belt	208/230	35	3	670,000	585,000	210°F	64"	28"	58"	1000
ST-507	6.7	500	4	Belt	208/230	22	1	1,200,000	1,100,000	300°F/ Steam	84"	36"	84"	2078
ST-2210	10	2200	15	Belt	208/230	42	3	1,000,000	920,000	210°F	84"	36"	84"	2115
ST-2512	12	2500	20	Belt	208/230	54	3	1,200,000	1,100,000	210°F	84"	36"	84"	2500
ST-2304-CT	4	2300	6	Clutch	208/230	20/15	1/3	350,000	175,000	210°F	56"	24"	55"	776
ST-3004-CT	4	3000	8/7.5	Clutch	208/230	30/25	1/3	350,000	175,000	210°F	56"	24"	55"	794
ST-2305-CT	5	2300	8/7.5	Clutch	208/230	30/25	1/3	420,000	175,000	210°F	56"	24"	55"	848
ST-3005-CT	5	3000	10	Clutch	208/230	30	3	420,000	175,000	210°F	56"	24"	55"	848
ST-3006-CT	6	3000	15	Clutch	208/230	35	3	585,000	175,000	210°F	64"	28"	58"	1000

**Limited Lifetime
Coil Warranty**

OPTIONS

- Clutch Drive Pump
- Multi-Gun Systems
- Onboard Fuel Tank (Oil Fired Units)
- 440V – 3 Phase
- Water Tight Remote Control Boxes
- Wall Mount Hose Reels
- High Impact Turbo Nozzle
- Downstream Detergent Injection
- Additional Hose Lengths
- Various Wand Lengths
- Telescopic Extendable Wand
- Wet Sandblast Kit
- Drain Cleaning / Culvert Thawing Kit
- Scalesafe Water Treatment System

FEATURES

- ½" or ¾" Schedule 80 Steel Heating Coil
- Stainless Steel Combustion Chamber
- Beckett Burner System (Oil Fired Units)
- Racor Fuel Water Separating Filter (Oil Fired Units)
- Electronic Ignition (Gas Fired Units)
- Automatic Timed Shutdown
- Stainless Steel Float Tank
- Corrosion Free Float Valve
- Belt-Drive Triplex Plunger Pump
- High Pressure Soap Injection
- High Limit & Low Water Shutdown
- Safety Relief Valve
- Adjustable Temperature Control
- Lighted Diagnostic Control Panel
- Hour Meter
- Solenoid Controlled Soap On/Off
- Prewired For Full Function Remote Control
- Low Voltage Control Wiring
- Hardened Stainless Steel Spray Nozzles
- Durable Powdercoat Frame
- Draft Diverter (Gas Fired Models)
- Industrial Grade Trigger Gun Assembly
- 50' Industrial Grade High Pressure Hose

A Closer Look at the Features:

Durable Powder Coated Heavy Duty Modular Frame
For years of maintenance free service and protection of the units internal parts.

Adjustable Temp. Control
For your precise temp. control.

Exclusive Coil Design
Heats water quicker & more efficiently.

Stainless Steel Combustion Chamber
Maintenance free, durable protection.

High Efficiency Burner
Conserves fuel & your dollars.

Panel Mounted Controls
Handy and accessible for your ease of use.

Hour Meter
Allows you to keep track for periodic maintenance.

Stainless Steel Nozzles
Panel mounted to be handy and accessible.

Soap Control
Allows for the precise metering of your soap.

Optional Clutch Drive
Save money by lengthening the life of your pump.

Heavy Duty Electric Motor
Built strong to handle your roughest demands.

Industrial Strength Triplex Pump
Lower maintenance costs due to long life & durability.

Pressure Relief Valve
Prevents injury and cost due to an over-pressurized system.

www.powereagleusa.com